

High Quality Laundry Equipment



Washer extractors



HS 6008



HS 4012



HS 6013



HS 6017



HS 4022

Description

The washer extractors are designed for a long life span and not comparable with household machines. These industrial machines are used among other things in commercial laundries, old and nursing homes, laundromat, penal institutions, sport associations, hotel etc..

The internal and external drums as well as the front linings are made of high-quality high-grade steel; the bearing of the drum is oversized and provided with a solid wave sealing.

The washer extractors of the series 6008, 6013 and 6017 have perforated driver ribs (Aquafall) integrated in the drum, whereby additional caustic solution and water arrive cascade-like at the laundry. By this system the washing capacity increases while the rinsing processes can be shortened.

All machines are equipped with a frequency converter (inverter - Gdrive) so that different drum speeds during washing or centrifugal process can be controlled.

The specified washer extractors have proven electronic controls. For more information about the different available systems (standard, free programmable or coin control versions) please refer to our offers and technical information.

With our free programmable controls professional wash sets can be achieved, such as "wet cleaning" for washable clothing, "cool-down" for mixed textures, etc...

The dosage of the liquid or pulverized detergents is made manually by cups or rinsing chambers. External dosing entrances for liquid detergents are basically present.

The aquamixer, a cold and warm water mixer delivers the preset temperature with a high grade of accuracy.

The washer extractors of series HS 4040 and HS 4055 have a capacity of 40 kg and/or. 55 kg of Tr. W. The HS 4055 is also available in the tilting version whereby the discharge process is substantially facilitated.

Please contact us for further technical information.

Technical data:

Type:	HS 6008
Capacity:	8 kg, 1:10
Drum diameter:	536 mm
Drum depth:	351 mm
Drum volume	79 Liter
Washing speed:	50 UpM
Centrifugal speed:	580,690,780,970
Heating:	electric
Width:	685 mm
Depth:	700 mm
<u>Height:</u>	<u>1080 mm</u>

Type:	HS 4012
Capacity:	12 kg, 1:10
Drum diameter:	580 mm
Drum depth:	450 mm
Drum volume	119 Liter
Washing speed:	47 UpM
Centrifugal speed:	1000 UpM
Heating:	electric or steam
Width:	756 mm
Depth:	920 mm
<u>Height:</u>	<u>1268 mm</u>

Type:	HS 6013
Capacity:	13 kg, 1:10
Drum diameter:	620 mm
Drum depth:	416 mm
Drum volume;	126 Liter
Washing speed:	25-49 UpM
Centrifugal speed:	400, 600, 800, 1005 UpM
Heating:	electric or steam
Width:	796 mm
Depth:	870 mm
<u>Height:</u>	<u>1325 mm</u>

Type:	HS 6017
Capacity:	17 kg, 1:10
Drum diameter:	700 mm
Drum depth:	450 mm
Drum volume:	173 Liter
Washing speed:	25-45 UpM
Centrifugal speed:	350,550,750, 950 UpM
Heating:	electric or steam
Width:	868 mm
Depth:	962 mm
<u>Height:</u>	<u>1404 mm</u>

Type:	HS 4022
Capacity:	23 kg, 1:10
Drum diameter:	740 mm
Drum depth:	530 mm
Drum volume:	228 Liter
Washing speed:	15-44 UpM
Centrifugal speed:	917 UpM
Heating:	electric or steam
Width:	1000 mm
Depth:	1200 mm
Height:	1420 mm